





REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2017/12/15	Arvin Chan	Change Rev.01 To Rev.A
B	LEN1840025~9	2018/03/19	Jason Yu	Modify Note & Update Box


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



MSAS: M12 A Code Shield
MSBS: M12 B Code Shield
MSDS: M12 D Code Shield

03: 3Pin
04: 4Pin
05: 5Pin
08: 8Pin

P: Panel
F: Female Connector




UNIT:mm		
TOLERANCE		
.X	± 0.25	
.XX	± 0.1	
.XXX	± 0.05	
ANGLES	$\pm 1^\circ$	




TITLE MI2 F CONN F PIN SMT TYPE			
SCALE	SIZE	SHEET	OF
1:1	A4	1	4
REV. B	WC-REV. A.2	(QC) Inspection item	

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
MSXS-XXPFET-EE8XXX	Jason Yu	2018/03/19
CUSTOMER	CHECKED BY	DATE
ALTW	Arvin Chan	2018/03/19
APPROVED BY		DATE
Kevin Hu		2018/03/19




- Note:
- * Important Dimension, Material Specification :
 - * Housing : Thermoplastic
 - * Female Pin : Copper Alloy, Gold Plated
 - * Ground : Copper Alloy, Tin Plated
 - * Spring : Stainless Steel
 - * O-Ring : Silicone, Black
- Electrical Specification :
- * Contact Resistance : $10\text{m}\Omega$ Max.
 - * Insulation Resistance : $100\text{M}\Omega$ min.
 - * Dielectric Withstanding Voltage : 1KV
 - * Rated Voltage : 3Pin&4Pin 250V d.c. or a.c.
5Pin 60V d.c. or a.c.
8Pin 30V d.c. or a.c.
 - * Rated Current : 3Pin, 4Pin&5Pin 4A
8Pin 2A
- Mechanical Specification :
- * Durability : 1000 Cycles(IEC : 100 Cycles)
 - * Environmental Specification :
 - * Temperature Range : $-55\text{~}125^\circ\text{C}$
 - * Salt Spray : 48h
 - * SMT Temperature & Time : $260^\circ\text{C}/5\text{Sec}$
 - * SMT Paste : 0.12mm min.



Amphenol LTW
安費諾亮泰企業股份有限公司





UNIT:mm			TITLE M12 F CONN F PIN SMT TYPE			Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO.	DRAWN BY Jason Yu	DATE 2018/03/19
TOLERANCE	±0.25		SCALE 1:1	SIZE A4	SHEET 2 OF 4			DWG NO. MSXS-XXPFT-EE8XXX	CHECKED BY Arvin Chan	DATE 2018/03/19
X	±0.1		REV. B	WC-REV. .0	(QC) Inspection item	CUSTOMER ALTW	APPROVED BY Kevin Hu	DATE 2018/03/19		
XX	±0.05									
XXX	±0.05									
ANGLES	±1°									
			2	3	4	5	6	7	8 W10814-03-WM01A2	



NOTE:
① Connector Orient follow Drawing



UNIT:mm			TITLE M12 F CONN F PIN SMT TYPE			Amphenol LTW 安費諾亮泰企業股份有限公司	ITEM NO	DRAWN BY Jason Yu	DATE 2018/03/19
TOLERANCE	.X ± 0.25	.XX ± 0.1	SCALE 1:1	SIZE A4	SHEET 3 OF 4		DWG NO MSXS-XXPFET-EE8XXX	CHECKED BY Arvin Chan	DATE 2018/03/19
ANGLES	.XXX ± 0.05	ANGLES ± 1°	REV. B	WC-REV. .0	①: Inspection item	CUSTOMER ALTW	APPROVED BY Kevin Hu	DATE 2018/03/19	
			2	3	4	5	6	7	8 W10814-03-A01A2



Note:
100 PCS(Connector)/Tape&Reel Put in a Box
5PCS(Max.) Box Put in a Carton



UNIT:mm		TITLE MI2 F CONN F PIN SMT TYPE			Amphenol LTW		ITEM NO	DRAWN BY	DATE
TOLERANCE		SCALE	SIZE	SHEET	OF	QC: Inspection item	DWG NO	CHECKED BY	DATE
.X	± 0.25	1 : 1	A4	4	4		MSXS-XXPFET-EE8XXX	Arvin Chan	2018/03/19
.XX	± 0.1						CUSTOMER	Kevin Hu	2018/03/19
.XXX	± 0.05	REV.	B	WC-REV.	.0		APPROVED BY		2018/03/19
ANGLES	$\pm 1^\circ$								