


DIGITUS Professional CAT 5e U/UTP patch cord

DK-1512-020/WH
EAN 4016032318033



CAT 5e U-UTP patch cable, PVC AWG 26/7, length 2 m, color white

The DIGITUS® Category 5e Class D patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 5e specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 5e cabling. The performance is tested up to 100 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 5e, because of the transparent blue colored connector.

Best performance and link quality for your network.

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection

- Length marking on boot
- Cable type: U/UTP
- Category: 5E
- Length: 2 m
- Type of connector connection 1: RJ45 8(8)
- Type of connector connection 2: RJ45 8(8)
- Colour outer sheath: White
- Anti-kink sleeve: Moulded-on
- Locking lever: yes
- Colour anti-kink sleeve: White
- Fire retardant version: no
- Halogen free: no
- Oil resistant (acc. EN 60811-404): no
- Cable construction: 4x2
- AWG-size: 26
- Pin assignment: 1:1
- NVP value: 69 %

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	150	7.50	36.00	36.00	24.00	31,104.00
Packaging Unit Inside	10	0.50	6.00	25.00	42.00	6,300.00
Packaging Unit Single	1	0.05	1.20	14.00	25.00	420.00
Net single without Packaging	1	0.04	200.00	1.17	1.27	297.18