

### product description



Flexible bus cable (4-core), sold by the meter, unassembled

Industrial Ethernet FC TP flexible cable, GP 2x2 (PROFINET Type B), TP installation cable with flexible cores, PROFINET type B, 4-core, shielded, CAT 5e, sold by the meter, delivery unit max. 2500 m minimum order quantity 20 m.

### suitability for use

For occasionally moved machine parts

### cable designation

2YY (ST) CY 2x2x0,75/1,5-100 LI GN SF/UTP

### electrical data

#### attenuation factor per length

- at 10 MHz / maximum 0.06 dB/m
- at 100 MHz / maximum 0.21 dB/m

#### impedance

- at 1 MHz ... 100 MHz 100 Ω

#### relative symmetrical tolerance

- of the characteristic impedance at 1 MHz ... 100 MHz 5 %

#### near-end crosstalk per length

- at 1 MHz ... 100 MHz 0.5 dB/m

#### transfer impedance per length / at 10 MHz

20 mΩ/m

#### loop resistance per length / maximum

120 mΩ/m

#### operating voltage

- RMS value 80 V

#### NVP value in percent

69 %

### mechanical data

#### number of electrical cores

4

#### design of the shield

Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires

#### type of electrical connection / FastConnect

Yes

#### core diameter

- of AWG22 insulated conductor 0.75 mm

#### outer diameter

- of inner conductor 0.75 mm
- of the wire insulation 1.5 mm
- of the inner sheath of the cable 3.9 mm
- of cable sheath 6.5 mm

#### symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

#### material

- of the wire insulation polyethylene (PE)
- of the inner sheath of the cable PVC
- of cable sheath PVC

#### color

- of the insulation of data wires white/yellow/blue/orange
- of cable sheath green

#### bending radius

- with single bend / minimum permissible 32.5 mm

|  |  |
|--|--|
| • with multiple bends / minimum permissible                              | 52 mm  |
| tensile load / maximum   | 150 N  |
| weight per length  | 68 kg/km   |
| <b>ambient conditions</b>  |  |
| ambient temperature  |  |
| • during operation   | -25 ... +75 °C   |
| • during storage   | -25 ... +75 °C   |
| • during transport   | -25 ... +75 °C   |
| • during installation  | -10 ... +60 °C   |
| • note   | Electrical properties measured at 20 °C, tests according to DIN VDE 0472   |
| fire behavior  | flame resistant according to UL 1685 (CSA FT 4)  |
| class of burning behaviour / according to EN 13501-6                     | Eca  |
| chemical resistance  |  |
| • to mineral oil   | oil resistant according to IEC 60811-404 (7x24h/90°C)  |
| • to grease  | Conditional resistance   |
| • to water   | conditional resistance   |
| radiological resistance / to UV radiation                                | resistant  |
| <b>product features, product functions, product components / general</b> |  |
| product feature  |  |
| • halogen-free   | No   |
| • silicon-free   | Yes  |
| wire length / for Industrial Ethernet                                    |  |
| • with 100BaseTX   | 85 m   |
| <b>standards, specifications, approvals</b>                              |  |
| UL/ETL listing / 300 V Rating  | Yes; c(ETL)us, CMG / (ETL)us PLTC / Sun Res / OIL RES  |
| UL/ETL style / 600 V Rating  | Yes; cRUus AWM 21694 AWM I A/B 60°C 600V FT2   |
| certificate of suitability   |  |
| • EAC approval   | Yes  |
| • CE marking   | Yes  |
| • RoHS conformity  | Yes  |
| standard for structured cabling  | Cat5e  |
| Marine classification association  |  |
| • American Bureau of Shipping Europe Ltd. (ABS)                          | No   |
| • French marine classification society (BV)                              | No   |
| • Det Norske Veritas (DNV)   | No   |
| • Germanische Lloyd (GL)   | No   |
| • Lloyds Register of Shipping (LRS)                                      | No   |
| • Nippon Kaiji Kyokai (NK)   | No   |
| • Polski Rejestr Statkow (PRS)   | No   |
| reference code   |  |
| • according to IEC 81346-2   | WG   |
| • according to IEC 81346-2:2019  | WGB  |
| <b>further information / internet links</b>                              |  |
| internet link  |  |
| • to website: Selection guide for cables and connectors                  | <a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>  |
| • to web page: selection aid TIA Selection Tool                          | <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>  |
| • to web page: SiePortal   | <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>  |
| • to website: Image database   | <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>  |
| • to website: CAX-Download-Manager                                       | <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>  |
| • to website: Industry Online Support                                    | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>  |
| <b>security information</b>  |  |
| security information   | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions |

undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

| General Product Approval | Environment |
|--------------------------|-------------|
|--------------------------|-------------|

[Manufacturer Declaration](#)

  
EG-Konf.



[Declaration of Conformity](#)

  
CCC

[Confirmation](#)

| Environment | Industrial Communication |
|-------------|--------------------------|
|-------------|--------------------------|

  
EPD

[PROFINET](#)

last modified:

8/8/2024 