


PCB Terminal Blocks

10.16 mm Pitch, Low Profile



Low profile

Polarised Mouldings

Guided pin alignment

Pin/terminal - tin plated brass

Wire clamp - nickel plated brass

Screw/torque - M2.5 steel Ni plated

Recommended PCB hole size $\varnothing 1.3$ mm

SPECIFICATION:

Pitch	10.16 mm
Termination type	Clamp Terminals/Screw Connection
Connection direction	horizontal
Rated current to EN	10 A
Rated current to UL	10 A
Rated voltage to EN	300 V
Rated voltage to UL	300 V
Connection cross-section	0.13-1.31 mm ² (26-16 AWG)
Colour	green
Temperature range	-33...+120 °C
Width	8.45 mm
Height	10 mm
Material	PA 66, UL94-V0

PRODUCT RANGE:

Art. Nr.	Poles	Length
RND 205-00243	2	15.2 mm
RND 205-00244	3	24.6 mm
RND 205-00245	4	34.76 mm
RND 205-00246	5	44.92 mm
RND 205-00247	6	55.8 mm
RND 205-00248	7	65.24 mm
RND 205-00249	8	75.4 mm
RND 205-00250	9	85.56 mm
RND 205-00251	10	95.72 mm
RND 205-00252	11	105.88 mm
RND 205-00253	12	116.04 mm